★ BAILIFF ENTERPRISES, INC. ★

CPVC BULKHEAD FLANGE



Screw-on CPVC bulkhead FLANGES offer safe, quick pipe connections for standard wall plastic tanks. We use Spears Schedule 80 bulkheads or their equivalent for our CPVC bulkheads. They are rated to 150 PSI. They offer left hand threads on the tightening ring to keep from loosening.

- The bulkheads are available in Thread by Thread (TxT), Thread by Socket (TxS) and Socket by Socket (SxS) variations. Our default is Thread by Thread unless otherwise specified. The threaded bulkheads use National Pipe Threads (NPT). -- These bulkheads are all available with EPDM or FPM (Viton) gaskets. Other gasket materials may optionally be sourced.
- They are available in 1/2", 3/4", 1", 1-1/2" 2", 3" 4" and 6" pipe sizes. Some of the larger sizes are not available on small diameter tanks.

When connecting threaded fittings, be sure to use Teflon (PTFE) impregnated plumbers paste rather than Teflon tape. Teflon tape can bunch up an cause a fitting to crack.

BAILIFF ENTERPRISES, INC. ◆ 305 E. Rogers Road ◆ Willis, TX 77378
Contact Dan Miller ◆ 936-228-1520 ◆ dmiller@plasticstoragetanks.com